



JMI PUMP SYSTEMS

Your Partners in Pumping Since 1958

W194 N11695 McCormick Drive

Germantown, WI 53022

262-253-1353 • 800-234-5490

www.jmipumps.com • sales@jmipumps.com

SINK TRAY SANITARY PUMP SYSTEM

Model PVL-WATERBOX-03

FEATURES

- The 1/3 HP, 3/8" solid handling, pump (Model PVL-PRO-33V) has a cast iron housing for quiet operation.
- Pump uses vertical style switch w/piggy-back plug
- 6 gallon capacity basin is made of polypropylene, light weight and corrosion resistant and comes with a reusable pvc seal (Gas Tight)
- Sits on floor, under cabinets – no digging
- Pre-assembled and ready to install
- Basin Dimensions: 13-3/8"H x15-1/16"W
- Inlet: 1-1/2" FNPT @11-9/16" (measured from bottom of basin to center of inlet)
- Basin Cover: 1-1/2" FNPT discharge & 1-1/2" FNPT vent openings
- 2 year limited warranty



APPLICATIONS:

For use with bar sinks, laundry sinks, utility sinks, dehumidifiers, condensate, air conditioners, etc.

SPECIFICATIONS

HORSEPOWER	1/3
VOLTS	115
POWER CORD	10'
RPM	1550
FULL LOAD AMPS	4.3
SOLID HANDLING	3/8"

CONSTRUCTION

DISCHARGE	1-1/2"
MOTOR HOUSING	Epoxy Coated / Cast Iron
SWITCH	VerticalMaster
IMPELLER TYPE / MATERIAL	Vortex / Cast Iron
VOLUTE	Epoxy Coated Cast Iron
POWER CORD	SJTW-A
MECHANICAL SHAFT SEAL	Nitrile w/ carbon & ceramic face
FASTENERS	Stainless Steel
SHAFT	Cold Rolled Steel
UPPER & LOWER BEARINGS	Single Row, Ball, Oil Lubricated

PERFORMANCE CURVE

