WS Sewage Series



CSA 108 UL 778




Applications

• Ideal for handling raw sewage as well as commercial dewatering sump applications with up to 2" solids.


Features

- 1/2 hp and 1 hp oil filled chamber with double ball bearing. Designed for hi-torque and is thermally protected with automatic reset (single-phase only)
- Motor shaft is stainless steel
- Motor and pump housing is cast iron
- 2" NPT discharge
- Mechanical carbon/ceramic seal
- Cast iron solids handling non-clog impeller
- Stainless steel fasteners throughout, for serviceability
- Mechanical float switch for automatic on-off operation; piggyback style
- Power cord sealed at motor housing

Engineering Data



Performance Data



*Dimensions measured in inches [mm]

Model	Α	В	C	D	E	F	G
WS51	1.75" [44.5]	13.25" [336.6]	5.25" [133.4]	2" [50.1]	12.25" [311.2]	4.68" [118.9]	9.38" [238.3]
WS52	1.75" [44.5]	14" [355.6]	6.38" [162.1]	2.31" [58.7]	12.25" [311.2]	4.68" [118.9]	9.38" [238.3]
WS52H	1.75" [44.5]	15.1" [383.6]	6.38" [162.1]	2.31" [58.7]	12.25" [311.2]	4.68" [118.9]	9.38" [238.3]
WS102	1.75" [44.5]	15.1" [383.6]	6.38" [162.1]	2.31" [58.7]	12.25" [311.2]	4.68" [118.9]	9.38" [238.3]
WS102H	1.75" [44.5]	15.1" [383.6]	6.38" [162.1]	2.31" [58.7]	12.25" [311.2]	4.68" [118.9]	9.38" [238.3]

Performance Chart

	RPM		Shut-Off						
Model No.		5'	10'	15'	20'	25'	30'	35'	Head (ft)
WS51	1750	155	120	83	52	-	-	ı	27
WS52	1750	135	90	56	14	-	-	1	23
WS52H	3450	156	128	97	68	32	-	1	29
WS102	1750	-	168	144	118	85	46	1	37
WS102H	3450	-	190	170	148	124	100	74	48

Specifications

Item No.	Model No.	Listing	НР	Volts	SFA	Phase	Solids Handling	Discharge	Switch	Cord Length (ft)	Ship Wt. (lbs)
			.,_								
620013	WS52M	cCSAus	1/2	115	11.6	1	2"	2"	Manual	20	57
620254	WS52HM	cCSAus	1/2	115	11.6	1	2"	2"	Manual	30	58
620256	WS52HM-12	cCSAus	1/2	208-230	11.6	1	2"	2"	Manual	30	58
620203	WS102M-12	cCSAus	1	208-230	9.8 - 10.7	1	2"	2"	Manual	20	62
620208	WS102M-32	cCSAus	1	208-230	4.30 - 4.58		2"	2"	Manual	20	63
620209 620258	WS102M-34 WS102HM-12	cCSAus cCSAus	1	460 230	2.15 13.3	3 1	2"	2"	Manual Manual	20 30	63 61



Franklin Electric

P.O. Box 12010 Oklahoma City, OK 73157-2010 Phone: 1.800.701.7894 Fax: 1.800.678.7867 www.LittleGiantPump.com



