

N116 W18455 Morse Drive Germantown, WI 53022 262.253.1353 / 800.234.5490 Fax 262.253.1248 www.jimmurrayinc.com

Sink Tray Sanitary Pump System Model PVL-WATERBOX-01



Applications: For use with bar sinks, laundry sinks, utility sinks, dehumidifiers, condensate and, air conditioners, etc.

Pump Specifications

Horsepower: 1/3	RPM: 1550
Volts: 115	Full Load Amps: 6.0
Cord: 10'	Solid Handling: 1/2"

Pump Construction

Cover	Polycarbonate
Motor Housing	Epoxy Coated Cast Iron
Impeller Type / Material	Vortex / Nylon
Volute	Epoxy Coated Cast Iron
Power Cord	SJTW-A
Mechanical Shaft Seal	Nitrile w/ carbon an ceramic face
Fasteners	Stainless Steel
Shaft	Cold Rolled Steel
Upper & Lower Bearings	Sintered Sleeve Bearings

Features and Benefits

- The 1/3 HP, 1/2" solid handling, Energy Savings pump (Model PVL-ES-SFS) has a cast iron housing with an epoxy coating for corrosion & rust resistance.
- Pump uses snap action style switch
- 6 gallon capacity basin is made of polypropylene, light weight and corrosion resistant and comes with a reusable PVC seal (Gas Tight)
- Sits on floor, under cabinets no digging
- Pre-assembled and ready to install
- Basin Dimensions: 13-3/8"H x15-1/16"W
- Inlet: 1-1/2" FNPT @11-9/16" (measured from bottom of basin to center of inlet)
- Basin Cover: 1-1/2" FNPT discharge & 1-1/2" FNPT vent openings
- 3 Year Limited Warranty

Performance Curve

